



# SCJ

## Spray Applied Bitumen Cold Joint Sealer

### Applications

Ultracrete SCJ, part of the Ultracrete BBA/HAPAS Approved Ironwork Reinstatement System, is a bitumen cold joint sealant spray, designed to seal and waterproof the vertical edges of macadam and asphalt within road and ironwork reinstatements. The product is ideal for promoting durability and longevity in temporary and permanent Ironwork reinstatements.

### Technical

Ultracrete SCJ is supplied in 750ml spray cans, with the bitumen being discharged by inverting the container and pressing the spray button.

### Preparation

Remove as much standing water and loose particles as possible prior to product application. The sealer can be applied to damp or dry surfaces.

### Application

Hold the can tightly and shake vigorously before use. Invert the can and press the spray button. Cover the area to be sealed with long strokes from a distance of 175mm to 250mm, working from the top downwards. Ensure that the entire surface is covered.

### Cleaning

Point nozzle upward immediately after use and spray for a few seconds to clear it, taking care not to spray into wind. Failure to clean the nozzle after use could result in the aerosol becoming blocked rendering the product unusable.

### Health & Safety

This product should not come into contact with the skin or eyes. Avoid inhalation of fumes and work in well-ventilated conditions. Protective clothing and gloves should be worn. The product can be removed from the skin by using soap and water, seek medical attention if discomfort continues. If swallowed, do not induce vomiting rinse mouth thoroughly with water if conscious and seek medical attention if discomfort continues. Note: This product is extremely flammable. The propellant in this may explode if exposed to excessive heat or naked flame. Do not pierce or burn. For an full updated Material Safety Data Sheet please visit [www.instarmac.co.uk](http://www.instarmac.co.uk)

### Disposal

Pressurised container. Do not pierce or burn, even after use.



### Features & Benefits

- Part of the Ultracrete BBA/HAPAS Approved Ironwork Reinstatement System
- Clean efficient use
- Eliminates the use of application brushes
- Can be used in all weather conditions
- Ozone friendly
- Simple and economical to apply
- Prevents water ingress instantly
- Prevents freeze thaw damage



### Related Products

**Ultracrete Envirobond HA104<sup>®</sup>** High Performance Bedding Mortar

**Ultracrete PY4** Polyester Resin Fast Setting Bedding Mortar

**Ultracrete M60** Rapid Strength Bedding Mortar

**Ultracrete QC10** Fast Set Rapid Strength Concrete

**Ultracrete IRR** Cold Lay Macadam

continued



# SCJ

## Spray Applied Bitumen Cold Joint Sealer

### Product Details

Unit/Packaging	Supplied in 750ml aerosol cans, 12 per box
Storage	Aerosol cans must NOT be exposed to direct sunlight or temperature above 50°C. Store in a cool well-ventilated place
Shelf Life	Shelf life in correct conditions for sealed goods is 12 months
Colour	Black

### Contact Us

**Instarmac® Group plc**, Birch Coppice Business Park, Danny Morson Way, Dordon, Tamworth, Staffordshire, B78 1SE, United Kingdom

Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466

Email: [email@instarmac.co.uk](mailto:email@instarmac.co.uk) Order: [orders@instarmac.co.uk](mailto:orders@instarmac.co.uk) Website: [www.instarmac.co.uk](http://www.instarmac.co.uk)

Ultracrete products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold subject to our conditions of sale, copies of which may be obtained on request.

An **INSTARMAC®** Brand