# TECHNICAL DATA SHEET : NO MORE ROT INSECTICIDE

**PRODUCT DESCRIPTION** 

Wykamol

No More Rot Insecticide is a ready to use, liquid timber treatment offering an effective solution to infestations of wood boring insects, such as woodworm, and preventing future re-infestation. Designed for interior by both the DIY and professional user to quickly complete a timber treatment in any property type. Due to the microscopic size of the active ingredient, No More Rot Insecticide is highly penetrating and therefore ultra-effective and longlasting.

# Wykam NSEACHD

Issue 1 2019 02 TTTDS05

#### **TYPICAL USES**

- Killing active infestations of wood boring insects such as woodworm (Anobium Punctatum)
- Prevents re-infestation of wood boring insects
- Doors
- Window Frames
- Fences
- Floorboards
- **Garden Furniture**
- Joists
- Sheds

## **DVANTAGES**

HIGHLY PENETRATING MICROEMULSION FORMULA

**ERADICATES AND PREVENTS INFESTATION OF WOOD** DESTROYING INSECTS

**EFFECTIVE AGAINST ALL LIFE STAGES OF WOOD BORING INSECTS. INCLUDING EGGS, LARVAE AND BEETLES** 

**SUITABLE FOR INTERIOR USE** 





CAN BE APPLIED USING BRUSH OR LOW PRESSURE SPRAY

# RTUALLY ODOURLESS



# QUICK DRYING

## THE WYKAMOL GROUP LTD Unit3, Boran Court, Network 65 Business Park, Hapton, Burnley, Lancashire BB1151H Tel:08454006666 Eax08454008888 Website:www.wykamol.com Gmail:info@wykamol.com

Technical Data Active Ingredients

PROPERTIES

Active ingreatents	
	SDS Sheet for further information)
VOC's	Low
HSE Number	10605
Colour	Clear
Packaging	Plastic
Coverage	Approx. 1 Litre/ 3 - 4 m <sup>2</sup>
Shelf Life	24 months from date of manufacture.
Storage	Store in a cool, well ventilated area,
	out of reach of children.
	Keep container tightly closed.

Permethrin (See

# SITE PREPARATION

Keep unprotected persons and animals away from the area where application will occur, and until surfaces are touch dry. Depending on substrate and ambient conditions, surfaces are usually touch dry after 1 hour. Ensure adequate ventilation during application.

## SUBSTRATE PREPARATION

Ensure that all timbers to be treated are clean and free from wood dust and other contaminants. Surfaces may be damp but not wet. If decay is present, remove all decayed wood and replace with suitably treated timber, or contact the Wykamol technical Department regarding our Timber repair systems.

# TECHNICAL DATA SHEET : NO MORE ROT INSECTICIDE

Issue 1 2019 02 TTTDS05

#### **APPLICATION**

Always consult the Safety Data Sheet before commencing application.

No More Rot Dual Insecticide can be applied using a brush, low pressure spray or dipping.

1. Shake well before use.

Wykamol

- 2. Perform a test on a small, inconspicuous area before commencing complete application to ensure product finish is as expected.
- 3. For application with low pressure spray or brush.
- 4. No More Rot Dual Purpose requires a two coat application. Apply at a rate of 1 Litre per 3 4 m<sup>2</sup>.
- 5. Allow the first coat to dry before applying the second.
- 6. Where possible dip the end grains of timber for a minimum of 3 minutes, otherwise us a good quality brush to work the product into the grains.

## **APPLICATION CONDITIONS AND LIMITATIONS**

Timber must not be in contact with ground.

#### **FINISHING**

Over coating can occur 24 hours after application, depending on the substrate and ambient temperatures.

## **CLEANING EQUIPTMENT**

Remove as much product as possible from the brush with a tissue, then wash the brush with soap and clean water.

#### PACK SIZE

Product Code: NMRINSRTU Pack Size: 5 Litre

#### **HEALTH AND SAFETY**

For further information and advice please contact the Wykamol Technical Department. Always consult the Safety Data Sheet which is available upon request or can be downloaded from our website.

Contains: Permethrin.

WARNING

Wear gloves, face mask and eye protection. Wash hand and exposed skin after use.



THEWYKAMOLGROUPLID Unit&,Boran Court,Network 65 Business Park, Hapton,Burnley,Laneashir@B3115111 Tel:03454006563 Fax03454003688 Website:www.way/temol.com email:Info@wyf.amol.com

- Ensure good ventilation during application process and until treatment is dry (HSE statutory 1 hour reentry time or until surfaces are dry). Drying times will vary based on ambient temperature.
- Avoid contact with skin and eyes and remove any splashes immediately.
- In roofs, felt under tiles must be protected from coming into contact with No More Rot Dual Purpose.
- Switch off electrical circuits in the area being treated, before application and for up to 48 hours after.
- PVC covered electrical wiring will not normally be effected, although we do recommend removing an excess prodyct from cables.
- Roof insulation MUST be removed and replaced only when timbers are thoroughly dry.
- Clean up spillages immediately with soapy water.